

# CO<sub>2</sub> MONITOR 2800 Carbon Dioxide Detection

and Warning Device






#### FIRST RESPONSE SYSTEM FOR CARBON DIOXIDE

Bacharach's CO<sub>2</sub> Monitor 2800 is a compact and lightweight Carbon Dioxide detection and warning device that immediately responds to excessive concentrations of CO<sub>2</sub>. The 2800 is based upon the principle of infrared absorption and has two preset alarm levels at 5,000ppm and 10,000ppm. When either of these levels is reached, audible and visual alarm signals are activated, sounding until the CO2 level drops below the preset level. It is the ideal instrument for agriculture, horticulture, nuclear power plants, food & beverage industry and for organizations concerned about indoor air quality.

#### Features & Benefits

- · Compact & lightweight
- Rapid detection of changing CO<sub>2</sub> levels
- Maintenance free dual wavelength infrared CO<sub>2</sub> sensor
- Visual and audible alarms
- 8 to 10 hours use on a full charge
- Quick, intelligent charge In less than two hours

- Automatic datalogging provides complete CO<sub>2</sub> exposure record
- Two way IrDA communication link
- Easy to read digital display
- · Easy calibration in fresh air
- Simple to use



### **Specifications**

| Range*            | $0-50,000$ ppm $CO_2$ $0-5\%$ $CO_2$                                    |
|-------------------|---|
| Resolution        | 100 ppm (0.01%CO <sub>2</sub> )   |
| Response Time     | T90<10 seconds @ 5,000 ppm and 10,000 ppm                               |
| Audible Alarm     | 85dB @ 0.5 meters   |
| Case Seal         | NEMA 12 (IP65); dust and water resistant                                |
| Power Source      | Nickel-metal hydride battery providing up to 10 hours of continuous use |
| Operating Temp.   | 32°F to 104°F (0°C to 40°C)   |
| Relative Humidity | 0 to 99% (non-condensing)   |
| Dimensions        | 5.5"L x 2.6"W x 0.8"H<br>(140 mm x 66 mm x 20 mm)                       |
| Weight            | 7 ounces (200 grams)  |
| Construction      | Hi Impact ABS case  |

<sup>\*</sup>Factory or user-selectable with optional software



## Ordering Information

| DESCRIPTION                  |
|------------------------------|
| CO <sub>2</sub> Monitor 2800 |
| IrDA Interface/Software      |
| In-car charger               |
| Earphone                     |
|                              |

| PART NO. | DESCRIPTION                                |
|----------|--|
| 19-3304  | Protective Boot                            |
| 19-3305  | Calibration Cup                            |
| 51-2978  | Calibration Kit                            |
| 54-0600  | Calibration Gas (340 ppm CO <sub>2</sub> ) |



World Headquarters: 625 Alpha Drive, Pittsburgh, PA 15238 phone: 1-800-736-4666 website: www.bacharach-inc.com

